









84" AND 94" DOZER BLADE

The Dozer Blade is a versitile attachment for dozing, leveling ground and general earthmoving work. Hydro electric controlled angle and tilt using only one loader valve.

Features:

- Available in Angle and Tilt, Angle only, and Fixed.
- Angle and Tilt cylinders are interchangeable and equipped with self aligning bushings.
- Reversible 3/4" x 200mm bolt-on cutting edge & formed moldboard 8mm thick & 700mm high.
- Large 3" center pivot pin with hardened steel bushings.
- Full length high carbon steel, replaceable skid shoe.
- Set up to default in either tilt or angle position.
- Universal skid-steer loader quick attach mounting.
- 2 year limited warranty.

Options:

- An electrical switch.
- Plug n go 8 pin skid steer connection.
- An electrical control box.

Ideal Use:

Earthmoving, landscaping, roadworks and more.

Machine Suitability:

Skid steer loaders, excavators, telehanders, backhoes and other specailised machines.

Specification:	84"	94"
Weight:	283Kg (fixed)	315Kg (fixed)
	xxxKg (Angle Only)	xxxKg (Angle Only)
	519Kg (Angle & Tilt)	590Kg (Angle & Tilt)
Length (O.A.L)	840mm	940mm
Height (overall)	725mm	762mm
Width (overall) (D)	2133mm	2400mm
Width at 15° angle *	2082mm	2318mm
Width at 30° angle (B) *	1880mm	2078mm
Angle left & right (E)*	30°	30°

^{*}Not applicable to fixed dozer blade DZ-000093 & DZ-000095



Also Available 48"Mini Tilt Dozer Blade

Contact your local professional dealer or contact Digga direct

THE BEST DOWNUNDER

PHONE: 1300 2 DIGGA EMAIL: info@digga.com

27 Metcalf Street

6/15 Yampi Way Willeton WA 6155

WEB: www.digga.com

